DOSATRON®

WATER POWERED DOSING TECHNOLOGY

SCHEMATICS

Dosatron Liquid Dispenser
Model #D07RE125 — 3 GPM
1:666 – 1:80
4.3 – 85 PSI
¾" NPT Connection

Suggested Installation:
200 mesh/80 micron water filter prior to unit
One-way check valve downstream from unit for water hammer protection


Suggested Maintenance Interval:
Replace injection seals every 12 months


DOSATRON SALES & SERVICE - NORTH & CENTRAL AMERICA

Dosatron International, Inc.
Phone: 727-443-5404 Service: (800) 523-8499
Fax: 727-447-0591
www.dosatronUSA.com

D07RE125

0.7 m^3/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi






Seal Kit Part # PJDI097 (For serial # <05370953)
 # PJDI106 (For serial # >05370953)

D07RE125/1005/D

D07RE125


0.7 m³/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi



D07RE125/1005/D

D07RE125

0.7 m³/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi




D07RE125/1005/D

C+M

D07RE125

0.7 m³/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi




D07RE125/1005/D

C+M

D07RE125

N° SERIE
(N° 05370953 ⇨)

0.7 m³/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi




D07RE125/1005/D

C+M

D07RE125

0.7 m³/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi




D07RE125/1005/D

C+M

D07RE125


0.7 m³/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi



D

D07RE125

0.7 m³/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi




D07RE125/1005/D

D

D07RE125

0.7 m³/h - 0.15 - 1.25%
*3 GPM - 1:*666 - *1:80*
0.3 - 6 bar
4.3 - 85 psi



A