

Dilution™

SOLUTIONS

A Dosatron International, Inc. Company

To order now, call 1-800-451-6628

Pressure Regulator

Part #:

- **PR34**
- **PR100**
- **PR112**

Product Specifications

Pressure reducing valves are devices which, when installed on water systems, decrease the pressure from incoming water lines.



Description	Part #
3/4" NPT. Female inlet and outlet, working pressure: 15-87 psi, max incoming pressure: 230 psi. Max temp: 140 °F. Chrome plated brass body with 2" face.	PR34



Description	Part #
1" FPT and/or 1 1/2" MPT. Comes with one 1" FPT union for easy installation and maintenance. Adjustable from 25-75 psi, set at 50 psi. Reduces pressure up to 400 psi. Brass body.	PR100



Description	Part #
1 1/2" FPT and/or 2" MPT. Comes with one 1 1/2" FPT union for easy installation and maintenance. Adjustable from 25-75 psi, set at 50 psi. Reduces pressure up to 400 psi. Brass body.	PR112

DilutionTM

SOLUTIONS

A Dosatron International, Inc. Company

To order now, call 1-800-451-6628

Pressure Gauge

Part #:

- **PG100**
- **PG160-MP-T**



Description	Part #
3/4" bottom mount only, 1/4" MPT, 1-100 psi, and 2" face. Designed to use with gas, oil, and water or any medium not corrosive to brass or bronze.	PG100



Description	Part #
2 1/2" face. 160 psi with max point. Includes extra needle that remains at the max pressure that was reached. Stainless steel.	PG160-MP-T

Pressure Gauge Kit

Part #:

- **PG100-34KIT - 3/4" FPT**
- **PG100-100KIT - 1" FPT**
- **PG100-150KIT - 1 1/2" FPT**



Description	Part #
2" face, includes T fitting reducer. 0-100 psi. Polypropylene.	PG100-34KIT-3/4" FPT PG100-100KIT-1" FPT PG100-150KIT-1 1/2" FPT