



DOSATRON®

An Ingersoll Rand Business

3 GPM: D07RE125

PRODUCT DESCRIPTION

The water-powered Dosatron D07RE125-3 GPM injector is easy to install with an Industrial Plumbing Kit (IPK34-3GPM) and has a flow of 0.02 to 3 GPM with a ratio range of 1:667 to 1:80.

PRODUCT SPECIFICATIONS

Dilution Range:	1:667 to 1:80 (0.15% to 1.25%)
Water Flow Range:	0.02 to 3 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	<ul style="list-style-type: none"> • Polypropylene (Standard Blue) • PVDF (White)
Dimensions:	10" x 4 1/2"
Weight:	2 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and quick start guide
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor



MAINTENANCE KITS

Injection Seal Kit (Part # PJDI106 - For serial # over 05370953) - For yearly maintenance

Call 800-523-8499 to order the Dosatron for your specific application



DOSATRON®

An Ingersoll Rand Business

3 GPM: D07RE125

Recommended Installation for Industrial Applications

IPK34 - 3 GPM Industrial Plumbing Kit



- 3/4" polypropylene single union ball valve
- 1/2" stainless steel ball valve
- 3/4" polypropylene 200 mesh tee filter
- 3/4" brass pressure regulator w/gauge
- 3/4" 3 GPM flow restrictor
- 3/4" polypropylene check valve
- 3/4" union schedule 80 PVC
- 3/4" x 2" polypropylene fittings
- 1/2" x 2" polypropylene fittings
- 1/2" x 1/2" barb fitting
- 3/4" male to 1/2" female reducer bushing
- 3/4" Tee
- 3/4" street elbows
- Roll of thread tape
- Instructions card
- Zip tie

Dosatron International
2090 Sunnysdale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatron.com