

11 GPM: D25RE09

PRODUCT DESCRIPTION

The water-powered Dosatron **D25RE09 - 11 GPM** injector is easy to install using the Industrial Plumbing Kit (IPK34-10GPM). It has a water flow range of 0.05 to 11 GPM with a dilution range of 1:1000 to 1:112.



Dilution Range:	1:1000 to 1:112 (0.1% to 0.9%)
Water Flow Range:	0.05 to 11 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	Polyacetal (Standard Blue)PVDF (White)
Dimensions:	14" x 6 1/4"
Weight:	4 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104 ^o F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and operating manual
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor



MAINTENANCE KITS

Mini-Maintenance Kit (Part #: PJ127MINI-H) - For regular maintenance

Injection Seal Kit (Part #: PJ127) - For yearly maintenance

Call 800-523-8499 to order the Dosatron for your specific application



11 GPM: D25RE09

Recommended Installation for Industrial Applications

IPK34 - 10 GPM Industrial Plumbing Kit



3/4" polypropylene single union ball valve

1/2" stainless steel ball valve

3/4" poly 200 mesh tee filter

3/4" brass pressure regulator w/gauge

3/4" 10 GPM flow restrictor

3/4" polypropylene check valve

3/4" union schedule 80 PVC

3/4" x 2" polypropylene fittings

1/2" x 2" polypropylene fittings

1/2" x 1/2" barb fitting

3/4" male to 1/2" female reducer bushing

3/4" Tee

3/4" street elbows

Roll of Teflon tape

Instruction card

Zip tie

Dosatron International 2090 Sunnydale Blvd. • Clearwater, FL, USA 800-523-8499 • www.dosatronusa.com