



An Ingersoll Rand Business

# 11 GPM: D25RE5

## PRODUCT DESCRIPTION

The water-powered Dosatron D25RE5 - 11 GPM injector has a water flow range of 0.05 to 11 GPM and a dilution range of 1:100 to 1:20. It is easy to install with the Industrial Plumbing Kit (IPK34-10GPM).

## PRODUCT SPECIFICATIONS

Dilution Range:	1:100 to 1:20 (1% to 5%)
Water Flow Range:	0.05 to 11 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	Polyacetal (Standard Blue)
Other Options:	Side-inject
Dimensions:	14" x 6 1/4"
Weight:	4 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104 <sup>0</sup> F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and operating manual
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor



## MAINTENANCE KITS

Injection Seal Kit (Part #: PJ119) - For yearly maintenance

**Call 800-523-8499 to order the Dosatron for your specific application**



An Ingersoll Rand Business

# 11 GPM: D25RE5

## Recommended Installation

### IPK34 - 10 GPM Industrial Plumbing Kit



- 3/4" polypropylene single union ball valve
- 1/2" stainless steel ball valve
- 3/4" poly 200 mesh tee filter
- 3/4" brass pressure regulator w/gauge
- 3/4" 10 GPM flow restrictor
- 3/4" polypropylene check valve
- 3/4" union schedule 80 PVC
- 3/4" x 2" polypropylene fittings
- 1/2" x 2" polypropylene fittings
- 1/2" x 1/2" barb fitting
- 3/4" male to 1/2" female reducer bushing
- 3/4" Tee
- 3/4" street elbows
- Roll of Teflon tape
- Instruction card
- Zip tie

Dosatron International  
2090 Sunnydale Blvd. • Clearwater, FL, USA  
800-523-8499 • [www.dosatron.com](http://www.dosatron.com)

Dosatron International, LLC. is an industry leader in water-powered, proportional chemical injectors. Dosatron products are manufactured according to ISO 9001:2000 and ISO 14001:2004 standards.