

Dilution™ SOLUTIONS

To order call 1-800-451-6628

DLX(B) MF/M

SPECIFICATIONS

The **DLX MF/M** is a microprocessor controlled, multifunction metering pump. Operating modes include Digital Manual Mode, four Proportional Modes - signaled by a reed switch water meter, and a 4-20 mA input.

Other features include a backlit LCD display, Level Alarm, Relay Output, Flow Alarm, alarm for too many incoming signals, internal battery for power loss (up to 24 hours), buzzer, clock, remote control and timer.

230V and low voltage (12V and 24V) models are available upon request. 120V and 230V models are CSA certified.

DLXB models share the same features in a foot-mounted installation.

DLXB models with stroke length adjustment are available upon request.



DLX(B) Wetted Parts

Pump Head	PP (Polypropylene)
Diaphragm	PTFE (Teflon®)
Seals	FPM (Viton®) or EPDM (Dutral®)
Valves	Duck Bill FPM (Viton®) or EPDM (Dutral®)
Discharge Tubing	PE (Polyethylene)
Suction Tubing	PVC

DLXB Foot-Mounted model displayed.

Version	Flow Rate		Pressure		Strokes Per Minute
0115	0.26 GPH	1 LPH	217 PSI	15 BAR	120
	0.53 GPH	2 LPH	145 PSI	10 BAR	120
	0.79 GPH	3 LPH	72 PSI	5 BAR	120
0220	0.53 GPH	2 LPH	290 PSI	20 BAR	120
0507	1.32 GPH	5 LPH	101 PSI	7 BAR	120
	1.59 GPH	6 LPH	72 PSI	5 BAR	120
	2.11 GPH	8 LPH	29 PSI	2 BAR	120
0810	2.11 GPH	8 LPH	145 PSI	10 BAR	120
	2.64 GPH	10 LPH	101 PSI	7 BAR	120
	3.17 GPH	12 LPH	43 PSI	3 BAR	120
1504	3.96 GPH	15 LPH	58 PSI	4 BAR	120
2003	5.28 GPH	20 LPH	43 PSI	3 BAR	120