

14 GPM: D14TMZ10

PRODUCT DESCRIPTION

HOT-WATER Dosatron **D14TMZ10-14 GPM** is a precision water-powered unit that will operate with water temperatures up to 158 °F, for maximum cleaning effectiveness. Made of high-performance materials with a metal-free, re-enforced piston. High chemical compatibility.

PRODUCT SPECIFICATIONS

Dilution Range	1:100 to 1:10 (1% to 10%)
Water Flow Range	0.05 to 14 GPM
Operating Pressure Range	7 to 85 PSI
Housing Materials	PVDF
Other Options	Viscous
Dimensions	19 1/18" x 6 5/16"
Weight	8 lbs
Connection Size	3/4" NPT
Maximum Temperature	158 ^o F
Included Accessories	6' clear suction tube, strainer, weight, mounting bracket and quick start guide
Recommended Accessories	Pressure regulator, high-temperature 270 mesh filter, check valve, water-hammer arrestor



Injection Seal Kit (Part #: PJDI122) - For yearly maintenance

Injection Seal Kit for Viscous (Part #: PJDI122V) - For yearly maintenance





14 GPM: D14TMZ10

Recommended Installation for Industrial Applications

IPK34-14 GPM-WHA-HTEMP Industrial Plumbing Kit



- 3/4" stainless steel ball valve
- 3/4" stainless steel check valve
- 3/4" stainless steel water-hammer arrestor
- 3/4" brass pressure regulator w/gauge
- 3/4" CPVC high-temp filte

- 3/4" CPVC high-temp unions
- 3/4" CPVC high-temp close nipples
- 3/4" CPVC high-temp Tee
- Roll of thread tape

Dosatron International
2090 Sunnydale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatronusa.com