

To order now, call 1-800-451-6628

PKX FT/A

Product Specifications

The FT/A is an analog metering pump with manual flow control from 0 to 100%. It has two operating modes controlled by a reed switch water meter:

- Volumetric Proportional Mode - 1:1 (1 injection per 1 signal) as indicated by F Mode
- Volumetric Timer Mode - 0 to 60 seconds of metering per signal as indicated by T Mode

Level Alarm is available upon request.

The PKX dosing pump is compact and can be wall-mounted or foot-mounted.

PKX Wetted Parts	
Pump Head	PP (Polypropylene)
Diaphragm	PTFE (Teflon®)
Seals	FPM (Viton®) or EPDM (Dutral®)
Valves	Duck Bill FPM (Viton®) or EPDM (Dutral®)
Discharge Tubing	PE (Polyethylene)
Suction Tubing	PVC



ETATRON



Version	Flow Rate		Pressure		Strokes Per Minute
0105	0.26 GPH	1 LPH	72 PSI	5 BAR	120
0206	0.53 GPH	2 LPH	87 PSI	6 BAR	120
0505	1.32 GPH	5 LPH	72 PSI	5 BAR	120
0507	1.32 GPH	5 LPH	101 PSI	7 BAR	120
0702	1.85 GPH 2.64 GPH	7 LPH 10 LPH	29 PSI 14 PSI	2 BAR 1 BAR	120 120