

# Dilution™

## SOLUTIONS

A Dosatron International, Inc. Company

To order now, call 1-800-451-6628

## Pressure Regulator

Part #:

- **PR34-NPT**
- **PR100**
- **PR112**

### Product Specifications

Pressure reducing valves are devices which, when installed on water systems, decrease the pressure from incoming water lines.



Description	Part #
3/4" NPT low-lead brass body with durable stainless steel gauge with 1/8" brass threads. Female inlet and outlet, working pressure: 15-87 psi, max incoming pressure: 230 psi. Max temp: 140 °F. Includes one 3/4" FPT union for easy installation and maintenance.	PR34-NPT



Description	Part #
1" FPT and/or 1 1/2" MPT. Comes with one 1" FPT union for easy installation and maintenance. Adjustable from 25-75 psi, set at 50 psi. 400 psi maximum incoming pressure. Brass body.	PR100



Description	Part #
1 1/2" FPT and/or 2" MPT. Comes with one 1 1/2" FPT union for easy installation and maintenance. Adjustable from 25-75 psi, set at 50 psi. 400 psi maximum incoming pressure. Brass body.	PR112

# Dilution™

## SOLUTIONS

A Dosatron International, Inc. Company

To order now, call 1-800-451-6628

### Pressure Gauge

Part #:

- PG100-SS
- PG160-MP-T



Description	Part #
3/4" stainless steel gauge, bottom mount only, 1/4" brass threads, 0-100 psi, and 2" face. Reduces the risk of rust in wet/damp installations and extends the life of the component.	PG100-SS



Description	Part #
2 1/2" face. 160 psi with max pointer. Includes extra needle that remains at the max pressure that was reached. Stainless steel.	PG160-MP-T

### Pressure Gauge Kit

Part #:

- PG100-34KIT - 3/4" FPT
- PG100-100KIT - 1" FPT
- PG100-150KIT - 1 1/2" FPT



Description	Part #
2" face, includes T fitting reducer. 0-100 psi. Polypropylene.	PG100-34KIT-3/4" FPT PG100-100KIT-1" FPT PG100-150KIT-1 1/2" FPT