DOSERS REFERENCE CHARTS

Use these charts below to select the proper Dosatron Water-Powered Dosers to be used with your Nutrient Delivery System.

For more information or for any help selecting your dosers and kits that better suit your application, call **1-800-451-6628**, or CHAT with us @ **www.dilutionsolutions.com**.

Dosatron Doser Selection Chart

For use with Lo-Flo Series Water-Powered Nutrient Delivery System

Lo-Flo Series Flow Range: 2 to 10 GPM				N
MODEL	D25RE09VFBPHY	D14MZ3000VFBPHY	D14MZ2VFBPHY	D14MZ10VFBPHY
INJECTION RANGE	4 to 34 mL/gal	1.25 to 11 mL/gal	7.5 to 75 mL/gal	37.5 to 375 mL/gal
	0.1 to 0.9%	0.03 to 0.33%	0.2 to 2%	1 to 10%
MAX PRESSURE	85 PSI	85 PSI	85 PSI	85 PSI
CONNECTIONS	3/4" NPT	3/4" NPT	3/4" NPT	3/4" NPT

For use with Hi-Flo Series Water-Powered Nutrient Delivery System

Hi-Flo Series Flow Range: 5 to 40 GPM			
MODEL	D40MZ3000BPVFHY	D40MZ2BPVFHY	D40MZ5BPVFHY
INJECTION RANGE	1.25 to 7.5 mL/gal	7.5 to 75 mL/gal	37.5 to 190 mL/gal
	0.03 to 0.2%	0.2 to 2%	1 to 5%
MAX PRESSURE	116 PSI	116 PSI	116 PSI
CONNECTIONS	1 1/2" NPT	1 1/2" NPT	1 1/2" NPT

Dosatrons include: mounting bracket, suction hose, weighted strainer, one union*, and quick start guide. Please review the basic installation drawing for recommended accessories.

MAXIMUM TEMPERATURE: 104 °F. *Each doser comes with a single union to connect to the next doser or kit