

# Dilution™ SOLUTIONS

To order call 1-800-451-6628

## eOne MF

### SPECIFICATIONS

The **eOne MF** is a microprocessor controlled, multifunction metering pump, suitable for applications which require proportional dosing. The pump operates at a high dosing frequency (up to 300 impulses/minute) and is equipped with backlit graphic display for correct setting of the various programming parameters.

**eOne MF** features are:

- Digital Manual Control
- Level Control
- Proportional Dosing Modes (1 x n; 1 : n; 1 x n M; ml x l; L x l; ml x m3; PPM)
- Flow Rate Calibration
- Flow Sensor Input
- 4-20 mA control
- Pump Output Display
- Relay Output
- Underload/Overload alarms



**ETATRON**

#### eOne Wetted Parts

Pump Head	PVDF
Diaphragm	PTFE (Teflon®)
Seals	TFE/P (Aflas®)
Valves	Ceramic Ball
Discharge Tubing	PE (Polyethylene)
Suction Tubing	PVC

Version	Flow Rate		Pressure		Strokes Per Minute
	GPH	LPH	PSI	BAR	
0110	0.26	1	145	10	180
0216	0.53	2	232	16	300
0420	1.06	4	290	20	300
0607	1.59	6	101	7	300
0710	1.85	7	145	10	300
1012	2.64	10	174	12	300
1505	3.96	15	72	5	300
2007	5.28	20	101	7	300
3005	7.93	30	72	5	300